


# HGSMD

## UNCOUPLING MEMBRANE



**FLOOR HEATING SYSTEMS HAVE WELL-KNOWN ADVANTAGES, BUT THE UNCOUPLING MEMBRANE IS GAME-CHANGING.**

An uncoupling membrane has become a must-have to make heating cable installation easier. Its key purpose is to cut down on movement between the various materials used in a complete installation. The uncoupling membrane compensates for horizontal movements up to 1/8 in. which in turn protects tiles from cracking and delamination. Best of all, installing the heating cable is a snap!

### ■ EASY HEATING CABLE INSTALLATION

### ■ PROTECTS TILES FROM CRACKING AND DELAMINATION

### ■ MORE UNIFORM TRANSITION WITH ADJACENT NON-HEATED FLOOR COVERING

### ■ CAN REPLACE THE UNDERLAYMENT REQUIRED FOR TILING

### ■ SUBFLOOR VAPOUR MANAGEMENT

### ■ UNIFORM LOAD DISTRIBUTION

### ■ HEATING CABLE AND TILE INSTALLATION WITHOUT DRYING DELAY TIME

### MANUFACTURING

- Entirely made of polypropylene
- Rounded square studs for easy heating cable installation
- 3 rounded square studs spacing of 3 3/4 in. for optimal heat distribution and coverage
- Thermo welded woven back to increase the bond between the subfloor and membrane.
- Colour: blue
- Height of 1/4 in. (5.5 mm)
- Available in 53.8 ft<sup>2</sup> and 161 ft<sup>2</sup> rolls
- Available in 8.9 ft<sup>2</sup> sheets

### INSTALLATION

- Modified and non-modified mortars can be used as per mortar manufacturer recommendations
- Installation over plywood, OSB, concrete, gypsum base and

existing vinyl

- Installation possible directly over the subfloor (limitations apply)
- The membrane does not replace the need for movement joints
- Heating cable and tile installation without drying delay time

### COMPATIBLE FLOORINGS

- Ceramic, porcelain, stone, vinyl, laminated engineered wood
- Soft and wood floorings must be installed on a self-leveling underlayment layer of 1/2 in. on top of the studs.

### WARRANTY

- 25 years

#### IDEAL FOR:

bathroom, kitchen, living room,  
bedroom, basement, hallway

## TECHNICAL SPECIFICATIONS

PRODUCT	DESCRIPTION	WIDTH	LENGTH	SURFACE AREA COVERED
		IN.	FT	FT <sup>2</sup>
HGSMDF	uncoupling membrane sheet 8.9 ft <sup>2</sup>	39	2.75	8.9
HGSMD054	uncoupling membrane roll 54 ft <sup>2</sup>	39	16.4	54
HGSMD162	uncoupling membrane roll 162 ft <sup>2</sup>	39	49.5	162



Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).